


# Nutrix/20

Marchatura/Marking: **GR** NUTRIX/20 Ø INT x Ø EST REG. 10/2011  lotto



## Applicazioni/Application:

Idoneo per pulizia industriale e trasporto alimentare secondo il Regolamento UE nr. 10/2011, categorie A, B, C.

Ottima flessibilità. Copertura non sporchevole, scivolosa, di facile pulizia e resistente a oli e detersivi.

Idoneo per il passaggio di acqua calda in continuo fino a 70°C ad una pressione inferiore ai 20 bar.

Morbido e flessibile, risulta particolarmente adatto per utilizzo su avvolgitubo in contesti alimentari.

Esente da ftalati.

*For foodstuff and cleaning.*

*In compliance with reg. 10/2011, categories a-b-c. very flexible soft, easy to clean. resistant against oil, grease and detergents.*

*Suitable for the passage of hot water up to 70°C at W.P. inferior to 20 bar. Easy to assemble on hose reels.*

*Phthalate free.*



## Temperatura d'impiego/Temperature range:

- 15°C +70°C

## Costruzione/Construction:










- ① Copertura: PVC blu, morbido, non sporchevole. Resistente ai grassi.
- ② ④ Inserto tessile: poliestere alta tenacità.
- ③ Strato intermedio in PVC bianco, morbido.
- ⑤ Strato interno in PVC bianco, alimentare, resistente alle alte temperature.

① *Outer layer: blue, soft, grease proof PVC-P.*

② ④ *Reinforcement: polyester high strength.*

③ *Intermediate layer: white PVC-P.*

⑤ *Inner layer: white PVC-P for foodstuff; high temperature resistant.*

 mm	 mm	 mm	 mm	 Bar A 20° C	 Bar A 70° C	 Bar A 20° C	 Bar A 70° C	 g/m
12	20	4	80	33	20	100	60	240
16	24	4	90	33	20	100	60	340
19	28	3.5	110	33	20	100	60	450

